

IP65 Anti-Glare Downlight

Deep recessed design for superior glare control

Available in multiple wattages and colors to suit any project

Ideal for glare-sensitive environments like galleries, offices, and open air seating

Sleek, functional design combining performance with elegance

LED Downlights GALAX



Product Features

CCT : 2700K/3000K/3500K/4000K/
5000K/6500K/Tunable White/Dim to Warm
CRI : >80/>90/>95
Beam angle : 24°/36°/60°
Heatsink colour : Grey
Baffle colour : White/Black/Gun Black/
Brass/Rose Gold/Chrome

Material : Aluminium Die Casting
Mounting : Recessed
Dimming Options : TRIAC, DALI-2 DT6/DT8
IP Protection : IP65
External additional surge protection : Optional 10kV
Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%

While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

GALAX TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz

Operating input voltage : 100-300V AC, 50Hz

Operating Temperature : -10°C to +45°C

Power factor : >0.90

A-THD : <10%

Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature

Inbuilt surge protection : CM - DM : 3kV/4kV

GALAX 3W - 18W



MODEL NO. & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	CUT OUT	TOTAL LUMENS
TRDSLC 3W GALAX	3W	65MM	72MM	55MM	210 - 300 LUMENS
TRDSLC 6W GALAX	6W	65MM	72MM	55MM	420 - 600 LUMENS
TRDSLC 8W GALAX	8W	85MM	79MM	75MM	560 - 800 LUMENS
TRDSLC 10W GALAX	10W	85MM	79MM	75MM	700 - 1000 LUMENS
TRDSLC 12W GALAX	12W	85MM	79MM	75MM	840 - 1200 LUMENS
TRDSLC 15W GALAX	15W	105MM	94MM	95MM	1050 - 1500 LUMENS
TRDSLC 18W GALAX	18W	105MM	94MM	95MM	1260 - 1800 LUMENS