

Tilttable & Rotatable Surface Spotlight

Unique design allowing full tilt and rotation for flexible lighting control

Suitable for both accent and ambient lighting

LED Downlights ALASIA



Product Features

CCT : 2700K/3000K/3500K/4000K/
5000K/6500K/Tunable White/Dim to Warm
CRI : >80/>90/>95
Beam angle : 24°/40°/60°
Body colour : White/Black
Material : Aluminium Die Casting

Mounting : Surface-Mounted
Dimming Options : TRIAC, DALI-2 DT6/DT8
IP Protection : IP20
External additional surge protection : Optional 10kV
Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%

While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

ALASIA TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz
Operating input voltage : 100-300V AC, 50Hz
Operating Temperature : -10°C to +45°C
Power factor : >0.90
A-THD : <10%
Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature
Inbuilt surge protection : CM - DM : 3kV/4kV

ALASIA 6W - 14W



MODEL NO. & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	TOTAL LUMENS
TSDLCL 6W ALASIA	6W	80MM	90MM	420 - 600 LUMENS
TSDLCL 10W ALASIA	10W	80MM	90MM	700 - 1000 LUMENS
TSDLCL 12W ALASIA	12W	80MM	90MM	840 - 1200 LUMENS
TSDLCL 14W ALASIA	14W	80MM	90MM	1000 - 1400 LUMENS