

Compact IP65 Surface Spotlight

Sleek cylindrical design with IP65 protection for versatile indoor and semi-outdoor use

Compact form factor delivering powerful, focused illumination

Custom color options allow seamless integration with interior design themes

Ideal for outdoor spaces requiring durable yet aesthetic surface-mounted lighting

# LED Downlights MAGO



## Product Features

CCT : 2700K/3000K/3500K/4000K/  
5000K/6500K/Tunable White/Dim to Warm  
CRI : >80/>90/>95  
Beam angle : 20°/40°/60°  
Body colour : White/Black/Brown/Custom  
Honeycomb Louvre Option

Material : Aluminium Die Casting  
Mounting : Surface Mounted  
Dimming Options : TRIAC, DALI-2 DT6/DT8  
IP Protection : IP65  
External additional surge protection : Optional 10kV  
Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%

While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THNK** for the latest updates.

## MAGO TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz

Operating input voltage : 100-300V AC, 50Hz

Operating Temperature : -10°C to +45°C

Power factor : >0.90

A-THD : <10%

Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature

Inbuilt surge protection : CM - DM : 3kV/4kV

## MAGO 6W - 10W



MODEL NO & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	TOTAL LUMENS
TSDLCL 6W MAGO	6W	75MM	100MM	420 - 600 LUMENS
TSDLCL 10W MAGO	10W	75MM	100MM	700 - 1000 LUMENS