

Miniature Pinhole Spotlight

Precise beam angle for focused, accent lighting

Sleek, minimal design with tiny cutout size for discreet installation

Ideal for niche areas, miniature accents, and showcase lighting

Compact solution for functional and decorative lighting in interiors

LED Downlights PIXO



Product Features

CCT : 2700K/3000K/3500K/4000K/
5000K/6500K

CRI : >80/>90/>95

Beam angle : 15°/24°/36°

Body colour : White/Black/Silver

Material : Aluminium Die Casting

Mounting : Recessed

Dimming Options : TRIAC, DALI-2 DT6/DT8

IP Protection : IP20

External additional surge protection : Optional 10kV

Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%

While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

PIXO TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz

Operating input voltage : 100-300V AC, 50Hz

Operating Temperature : -10°C to +45°C

Power factor : >0.90

A-THD : <10%

Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature

Inbuilt surge protection : CM - DM : 3kV/4kV

PIXO 3W



MODEL NO & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	CUT OUT	TOTAL LUMENS
TRDSL3 3W PIXO	3W	40MM	54MM	35MM	210 - 300 LUMENS