

Miniature Telescopic Spotlight

Sleek telescopic design for modern interiors

Adjustable head allows precise aiming and focused illumination

Minimal cut-out size for discreet installation

Ideal for accenting artwork, displays, and architectural features

# LED Downlights TELIS



## Product Features

CCT : 2700K/3000K/3500K/4000K/  
5000K/6500K/Tunable White/Dim to Warm  
CRI : >80/>90/>95  
Beam angle : 15°/24°/36°  
Body colour : White/Black/Grey  
Material : Aluminium Die Casting

Mounting : Recessed  
Dimming Options : TRIAC, DALI-2 DT6/DT8  
IP Protection : IP20  
External additional surge protection : Optional 10kV  
Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%

While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THNK** for the latest updates.

## TELIS TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz

Operating input voltage : 100-300V AC, 50Hz

Operating Temperature : -10°C to +45°C

Power factor : >0.90

A-THD : <10%

Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature

Inbuilt surge protection : CM - DM : 3kV/4kV

## TELIS 8W - 12W



MODEL NO. & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	CUT OUT	TOTAL LUMENS
TRDSLC 8W TELIS	8W	85MM	105MM	75MM	560 - 800 LUMENS
TRDSLC 10W TELIS	10W	85MM	105MM	75MM	700 - 1000 LUMENS
TRDSLC 12W TELIS	12W	85MM	105MM	75MM	840 - 1200 LUMENS