

Adjustable Eyeball Spotlight

Adjustable head allows flexible and precise light direction

Low-glare design ensures comfortable visual experience

Ideal for highlighting walls, artwork, and architectural details

Sleek, minimalist design complements contemporary interiors

# LED Downlights AXIS



### Product Features

CCT : 2700K/3000K/3500K/4000K/  
5000K/6500K

CRI : >80/>90/>95

Beam angle : 15°/24°/36°

Body colour : White/Black

Material : Aluminium Die Casting

Mounting : Recessed

Dimming Options : TRIAC, DALI-2 DT6/DT8

IP Protection : IP20

External additional surge protection : Optional 10kV

Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%

While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THNK** for the latest updates.

## AXIS TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz

Operating input voltage : 100-300V AC, 50Hz

Operating Temperature : -10°C to +45°C

Power factor : >0.90

A-THD : <10%

Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature

Inbuilt surge protection : CM - DM : 3kV/4kV

## AXIS 3W



MODEL NO & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	CUT OUT	TOTAL LUMENS
TRDSL3C 3W AXIS	3W	34MM	80MM	30MM	210 - 300 LUMENS