

**Pull-Out Rotatable Spotlight**

Pull-out design for precise, targeted illumination

Can be used as a fixed spotlight or pulled out for adjustable lighting

Rotatable for flexible positioning and optimal coverage

Low-glare design ensures comfortable visual experience

# LED Downlights FLEXO



**Product Features**

CCT : 2700K/3000K/3500K/4000K/  
5000K/6500K/Tunable White/Dim to Warm  
CRI : >80/>90/>95  
Beam angle : 15°/24°/38°/60°  
Body colour : White/Black  
Tilt angle : 45°, 355° Rotation

Material : Aluminium Die Casting  
Mounting : Recessed  
Dimming Options : TRIAC, DALI-2 DT6/DT8  
IP Protection : IP20  
External additional surge protection : Optional 10kV  
Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%  
While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

## FLEXO TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz  
Operating input voltage : 100-300V AC, 50Hz  
Operating Temperature : -10°C to +45°C  
Power factor : >0.90  
A-THD : <10%  
Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature  
Inbuilt surge protection : CM - DM : 3kV/4kV

## FLEXO 8W - 12W



MODEL NO & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	CUT OUT	TOTAL LUMENS
TRDSLC 8W FLEXO	8W	103MM	120MM	90MM	560 - 800 LUMENS
TRDSLC 10W FLEXO	10W	103MM	120MM	90MM	700 - 1000 LUMENS
TRDSLC 12W FLEXO	12W	103MM	120MM	90MM	840 - 1200 LUMENS