

High-Wattage Surface Spotlight

Designed for double-height ceilings, delivering powerful and focused illumination

Available in IP44 and IP65 options for versatile semi-outdoor and outdoor applications

Medium and wide beam options ensure tailored lighting for different spaces

Combines high performance with clean, architectural design for modern interiors

LED Downlights STRATOS



Product Features

CCT : 2700K/3000K/3500K/4000K/
5000K/6500K/Tunable White/Dim to Warm
CRI : >80/>90/>95
Beam angle : 15°/24°/30°/38°/45°/60°
Body colour : White/Black
Material : Aluminium Die Casting

Mounting : Surface Mounted
Dimming Options : TRIAC, DALI-2 DT6/DT8
IP Protection : IP44/IP65
External additional surge protection : Optional 10kV
Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%
While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THNK** for the latest updates.

STRATOS TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz
Operating input voltage : 100-300V AC, 50Hz
Operating Temperature : -10°C to +45°C
Power factor : >0.90
A-THD : <10%
Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature
Inbuilt surge protection : CM - DM : 3kV/4kV

STRATOS 40W



MODEL NO. & DESCRIPTION	WATTAGE	OUTER DIAMETER	HEIGHT	TOTAL LUMENS
TRDSLC 40W STRATOS	40	140MM	165MM	2800 - 4000 LUMENS