

Non Magnetic Track Lights.
Tracklights for precise and reliable illumination.
Available in various wattages and baffle colours.
Sleek, minimal form complements modern architectural spaces.
Ideal for retail, office and hospitality applications.

LED Tracklights NEXIS



Product Features

CCT : 2700K/3000K/3500K/4000K/
5000K/6500K/Tunable White/Dim to Warm
CRI : >80/>90/>95
Beam angle : 36°
Body colour : White/Black/Brown/Custom
Baffle Colour : Piano Black/Chrome/Rose Gold/White
Channel : 2 Wire / 3 Wire

Material : Aluminium Die Casting
Mounting : Surface Mounted
Dimming Options : TRIAC, DALI-2 DT6/DT8
IP Protection : IP20
External additional surge protection : Optional 10kV
Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%
While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THNK** for the latest updates.

NEXIS TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz
Operating input voltage : 100-300V AC, 50Hz
Operating Temperature : -10°C to +45°C
Power factor : >0.90
A-THD : <10%
Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature
Inbuilt surge protection : CM - DM : 3kV/4kV

NEXIS 12-18W



| MODEL NO. & DESCRIPTION | WATTAGE | OUTER DIAMETER | HEIGHT | TOTAL LUMENS |
|-------------------------|---------|----------------|--------|--------------------|
| TSDLCL 12W NEXIS | 12 | 70MM | 150MM | 960 - 1200 LUMENS |
| TSDLCL 14W NEXIS | 14 | 70MM | 150MM | 1000 - 1400 LUMRNS |
| TSDLCL 18W NEXIS | 18 | 70MM | 150MM | 1440 - 1800 LUMENS |