

Soft, indirect illumination that creates a gentle halo glow on the wall
 Round, minimalist design that enhances modern and architectural interiors
 Provides smooth ambient lighting without glare or visible hotspots
 Ideal for creating warm, atmospheric effects in living, hospitality, and corridor spaces

LED Wall Lights VERSA



Product Features

CCT : 3000K
 CRI : >90
 Beam angle : 38°
 Body colour : Black
 Material : Aluminium Die Casting
 Mounting : Wall-Mounted
 IP Protection : IP65
 External additional surge protection : Optional 10kV
 Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%
 While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

VERSA TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz
 Operating input voltage : 100-300V AC, 50Hz
 Operating Temperature : -10°C to +45°C
 Power factor : >0.90
 A-THD : <10%
 Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature
 Inbuilt surge protection : CM - DM : 4kV

VERSA 12W



MODEL NO. & DESCRIPTION	WATTAGE	LENGTH x WIDTH	CRI	CCT	SPD	DRIVER
TSL 12W VERSA	6Wx2	192x80MM	90	3000K	OPTIONAL - EXTERNAL	INTERNAL