

Multi-faceted architectural form that adds subtle depth to any wall surface
 Uniform upward and downward beam for balanced visual impact
 Clean, minimal design offering a simple yet effective lighting solution
 Ideal for pathways, façades and modern interiors needing functional elegance

LED Wall Lights PRISM



Product Features

CCT : 3000K
 CRI : >90
 Beam angle : 38°
 Body colour : Black
 Material : Aluminium Die Casting & Mild Steel
 Mounting : Wall-Mounted
 IP Protection : IP65
 External additional surge protection : Optional 10kV
 Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%
 While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

PRISM TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz
 Operating input voltage : 100-300V AC, 50Hz
 Operating Temperature : -10°C to +45°C
 Power factor : >0.90
 A-THD : <10%
 Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature
 Inbuilt surge protection : CM - DM : 4kV

PRISM 12W



MODEL NO. & DESCRIPTION	WATTAGE	LENGTH x WIDTH	CRI	CCT	SPD	DRIVER
TSL 12W PRISM	6Wx2	160x80MM	90	3000K	OPTIONAL - EXTERNAL	INTERNAL