

Universal design delivering clean, functional up-down illumination  
 Versatile and minimal—ideal for terraces, walkways, and everyday architectural lighting  
 Provides balanced light distribution with a simple, modern aesthetic  
 A reliable, no-frills solution for practical outdoor and semi-outdoor spaces

# LED Wall Lights DUO SQ



### Product Features

CCT : 3000K  
 CRI : >90  
 Beam angle : 38°  
 Body colour : Black  
 Material : Aluminium Die Casting & Mild Steel  
 Mounting : Wall-Mounted  
 IP Protection : IP65  
 External additional surge protection : Optional 10kV  
 Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%  
 While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

## DUO SQ TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz  
 Operating input voltage : 100-300V AC, 50Hz  
 Operating Temperature : -10°C to +45°C  
 Power factor : >0.90  
 A-THD : <10%  
 Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature  
 Inbuilt surge protection : CM - DM : 4kV

## DUO SQ 12W



MODEL NO. & DESCRIPTION	WATTAGE	LENGTH x WIDTH	CRI	CCT	SPD	DRIVER
TSL 12W DUO SQ	6Wx2	200x100MM	90	3000K	OPTIONAL - EXTERNAL	INTERNAL