

A clean, compact cylindrical wall light designed for single-direction illumination
 Can be installed as either an uplight or a downlight, offering flexible application
 Minimal, modern form factor suited for terraces, corridors, and functional outdoor areas
 Delivers reliable, efficient lighting in a simple, no-frills design

LED Wall Lights SOLO



Product Features

CCT : 3000K
 CRI : >90
 Beam angle : 38°
 Body colour : Black/Brown
 Material : Aluminium Die Casting
 Mounting : Wall-Mounted
 IP Protection : IP65
 External additional surge protection : Optional 10kV
 Rated life (LM 80) : 50,000 hrs

Wattage tolerance = ±5%
 While this catalogue serves as a general guide, specifications and availability may change. Please verify with **THINK** for the latest updates.

SOLO TECHNICAL DATA



Rated input voltage : 240V AC, 50Hz
 Operating input voltage : 100-300V AC, 50Hz
 Operating Temperature : -10°C to +45°C
 Power factor : >0.90
 A-THD : <10%
 Driver type : Non Dim, Isolated, Service Life 30,000 Hours at max. temperature
 Inbuilt surge protection : CM - DM : 4kV

SOLO 7W - 12W



MODEL NO. & DESCRIPTION	WATTAGE	LENGTH x WIDTH	CRI	CCT	SPD	DRIVER
TSL 7W SOLO	7W	152x75 MM	90	3000K	OPTIONAL - EXTERNAL	INTERNAL
TSL 12W SOLO	12W	152x75 MM	90	3000K	OPTIONAL - EXTERNAL	INTERNAL